

Colorex Ltd 7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz www.colorex.co.nz

John Bull Himalaya 2.0 **Safety Boot**

Brand: John Bull \$224.00+GST

Options

Code	Description	Price
C4622-5	Size 5	\$224.00
C4622-13	Size 13	\$224.00
C4622-14	Size 14	\$224.00
C4622-7	Size 7	\$224.00
C4622-12	Size 12	\$224.00
C4622-10	Size 10	\$224.00
C4622-11	Size 11	\$224.00
C4622-8	Size 8	\$224.00
C4622-9	Size 9	\$224.00
C4622-6	Size 6	\$224.00

Description

John Bull Himalaya 2.0 Safety Boot - 4545

Claret Bullhide leather lace up safety boot

The most popular boot in the John Bull range - these are your general workhorse boot. The Himalaya can go anywhere and do anything.

With a bull bar too these are sure to quickly become your favourite boots - especially now they're adorned with the latest soling technology - CushionCore

Loved by construction workers, general tradies, electricians, landscapers, farmers, and workers in manufacturing, transport, heavy industry and mining.

Product Specification

& https://colorex.co.nz/shop/products/safety-personal-protection/foot-protection/john-bull-hima laya-2-0-safety-boot/ Page 1





Features:

- New CushionCore comfort technology absorbs and disperses energy as your heel strikes down while generating rebound at the front of your foot
- Dual-density midsole World first technology of two compounds skilfully injected into the midsole providing superior shock absorption at the heel and providing rebound at the forefront as you step
- TPU outsole with aggressive self-cleaning tread pattern providing superior grip, stability and abrasion resistance
- Super cushioning Comf2Bull airflow footbed of soft PU that's also antibacterial and washable
- Moulded PU Bull Bar scuff cap
- Extra heavy duty TPU toe guard for extra scuff protection
- Fully lined with padded collar and tongue
- Broad fitting 200 joule impact resistant type 1 steel toe cap
- Certified to Standard AS/NZS 2210.3.2009-Classification 1-ID 2815
- Certified to: Standard ASTM F2413-11 including electrical shock resistance (Clause 5.5)

Product Specification



