



Boss Fillers Medium Density Interior/Exterior Wood Filler

Brand: Boss

Options

Code	Description	Price
C1705-1	1L	\$26.00
C1705-2	4L	\$84.00

Description

Boss Fillers Medium Density Wood Filler

Boss Medium Density Wood Filler is an easy-to-use general purpose painters wood filler. The non-toxic single pack formula is environmentally friendly and makes it ideal for use in residential applications. Suitable for filling holes and imperfections in a variety of interior and exterior applications.

Features:

- Fast dry and non-shrinking
- Interior and exterior
- Paintable and stainable
- Excellent adhesion to a variety of substrates
- Super smooth finish and minimal slumping
- Long-lasting resistance to mildew and organic growth
- Easy sanding and excellent faring properties
- Minimal flashing
- Clean up with water.

Substrate Preparation:

All substrates must be dry and free from dust, dirt, mold and other contaminants which may affect adhesion. Exterior timber and fibre cement cavities should be primed prior to filling for best results. Concrete cavities should be sealed prior

Product Specification

<https://colorex.co.nz/shop/products/fillers-putties-silicones/rigid-fillers/boss-fillers-medium-density-wood-filler/>





to filling with a quality concrete sealer to prevent efflorescence and lime leaching.

Directions for Use:

Apply **Boss Medium Density Wood Filler** with a narrow filling blade. Take care to leave minimal excess filler around the hole and allow to dry. Ensure full cure has been reached prior to sanding and painting. Sand with 180 grit or finer sandpaper, remove dust, and prime with a quality water or oil-based primer undercoat followed by a quality topcoat. Do not allow prolonged exposure to sun or rain.

Applications:

Fills holes and imperfections in –

- Timber and fibre cement weatherboards and claddings.
- Timber trim, architraves, windows and door frames.
- MDF and wood-based composites.
- Concrete blocks, stucco and masonry.

Limitations:

- **Boss Medium Density Wood Filler** should not be subjected to prolonged exposure to rain or sun. Apply a high-quality paint as soon as practicable after curing.
- Not suitable for use with substrates which are permanently wet or subject to regular saturation.
- Fill larger holes by applying filler in multiple layers, allowing filler to cure between applications.

Safety and Storage:

- Keep contents out of reach of children.
- Store in a cool dry place out of direct sunlight for prolonged shelf life
- Content is non-hazardous and non-toxic.
- Dispose of empty container responsibly

Product Specification

🔗 <https://colorex.co.nz/shop/products/fillers-putties-silicones/rigid-fillers/boss-fillers-medium-density-wood-filler/>

