Colorex Ltd



7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz



Timbabuild EWS Wood Stabiliser 300ml

Brand:TimbaBuild **Code:** C3870-2

\$67.60 +GST \$77.74 incl. GST

Description

Timbabuild EWS Wood Stabiliser 300ml

Timbabuild Epoxy Wood Stabiliser is a specially designed two-part low viscosity, solvent free, resin primer which is designed to strengthen weakened wood fibres by penetrating deep into the wood. **EWS is designed to be used as a primer in conjunction with the Epoxy Rapid Cure (ERC10) or Epoxy High Build (EHB60) systems.** Once the damaged, decayed and discoloured wood has been removed by use of a suitable cutter tool such as a router or chisel, then the area to be treated is lightly sanded to ensure excellent adhesion. The moisture content of the wood should be no greater than 18% (check using a standard moisture meter) and damp wood should be allowed to dry naturally, or by way of a hot air gun. The two components are mixed manually into a separate container, and thoroughly agitated for one minute. The 2:1 mixing ratio should be strictly observed. EWS should be applied using a standard brush and left to cure for at least 20 minutes. **Use disposable paint brushes - cleaning is not possible after use.**

Key benefits

- Solvent Free suitable for indoors and outdoors
- Excellent Penetration due to the Low Viscosity
- Pre-measured to Volume 2:1 ratio to ensure accurate mix
- High Strength & Durability
- Fast and Simple to Use, Easy to Clean and Store
- Used with both the ERC10 & EHB60 systems





Colorex Ltd



7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz

Specifications

Estimated Coverage (Hard Wood)	2m2
Estimated Coverage (Soft Wood)	1.5m2
Estimated Coverage (Damaged Wood)	1.0m2

