

7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz



Selleys No More Gaps Professional XM3 475g

Brand:Selleys

Options

Code	Description	Price
C1282B	Carton (12)	\$96.15
C1282	Cartridge	\$8.85

Description

Selleys No More Gaps Professional XM3 475g

Selleys No More Gaps Multi-purpose is general-purpose interior / exterior flexible gap filler. Its water based formulation delivers superior flexibility & long term resistance to cracking & crumbling, giving you a lasting finish. This formulation makes it ideal for sealing or filling gaps and joints where expansion and contraction occurs such as between a skirting board and a wall, which can cause rigid fillers and other less flexible gap fillers to crack and fall out.

Features

- Superior flexibility to cope with building movement, meaning the cracks and gaps will be hidden for longer. Has greater than 300% elongation/stretch and up to +/- 15% movement capability.
- Superior adhesion to a broad range of surfaces, resulting in a lasting finish.
- A smooth flawless finish and minimal shrinkage from the sides of the gap or joint, to give you the professional look.
- Can be painted over with both water and oil based paints, after the surface has skinned. (Approximately 30 minutes after application). Wide joints are best left for 48 hours before painting as some paints shrink during drying that can cause the paint to crack.
- Is formulated for long term resistance to cracking and crumbling.
- Is water based, so can be cleaned up easily and quickly with water.
- Will not stain building materials.
- Has good resistance to weathering.

Specifications

Product Specification





Colorex Ltd



7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz

- Greater than 300% elongation/stretch
- Up to +/- 15% joint movement
- Tubes of 475g
- Colour white
- Paintable (both water-based and oil-based paints) approx. 30 minutes after application

