Colorex Ltd



7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz



Petzl ASAP + 40cm ASAP'sorber

Brand:Petzl Code: C6287

\$412.90 +GST \$474.84 incl. GST

Description

Petzl ASAP + 40cm ASAP'sorber

What's included

- Petzl ASAP Fall Arrester
- Petzl OK TRIACT-LOCK automatic locking carabiner
- Petzl ASAP'Sorber 40cm

Petzl ASAP

- Constant fall protection:
 - arrests falls, slides, and uncontrolled descents
 - works on vertical or angled rope
 - locks on the rope even if grabbed during the fall
- Simple to use, and effective:
 - moves up or down the rope, without any manual manipulation of the device
 - easy to install and remove at any point on the rope
 - it can be used with an energy absorber to work at a distance from the rope: the ASAP'SORBER European version or ASAP'SORBER AXESS allows uses of up to 250 kg in two-person rescue situations

Specifications

Product Specification





Colorex Ltd



7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz

- Materials: aluminum & stainless steel
- Weight: 370g (295 g for ASAP and 75g for OK TRIACT-LOCK)
- Certifications: CE EN 12841 type A when used with an ASAP'SORBER and an EN 1891 type A 10 to 13mm rope
- Certifications: CE EN 353-2 when used with an ASAP'SORBER nergy absorber and an AXIS 11mm or PARALLEL 10.5mm rope with a sewn termination
- Certifications: EAC when used with an ASAP'SORBER and an EN 1891 type A 10 to 13mm rope

Petzl ASAP'Sorber

- Connects the ASAP or ASAP LOCK mobile fall arrester to the harness
- Allows the user to keep the rope at a distance in order to:
 - Declutter the work area
 - Protect the rope from sharp tools and molten metal splash
- Absorb the energy of a fall by the tearing of specific stitching
- Zippered fabric pouch protects the energy absorber from abrasion and other damage while allowing for regular inspection of the absorber
- Ends equipped with STRING to hold the connector in position and protect the webbing from abrasion
- Available in two lengths for a choice of the best balance between distance from the rope and reducing the fall length

Specifications

- Materials: nylon & polyester
- Certifications: CE EN 12841 type A and CE EN 353-2 when used with an ASAP or ASAP LOCK mobile fall arrester
- Certifications: CE EN 355, EAC

