Colorex Ltd
7 Fitzherbert St, Petone, Wellington 5012
PO Box 38 453, Wellington Mail Centre 5045
Phone: 04 587 0400, Email: sales@colorex.co.nz
www.colorex.co.nz



Petzl ASAP + 40cm ASAP'sorber

Brand: Petzl
Code: C6287

$412.50 +GST $474.38 incl. GST

Description

Petzl ASAP + 40cm ASAP’sorber

What’s included

- Petzl ASAP Fall Arrester
- Petzl OK TRIACT-LOCK automatic locking carabiner
- Petzl ASAP’Sorber 40cm

Petzl ASAP

- Constant fall protection:
  – arrests falls, slides, and uncontrolled descents
  – works on vertical or angled rope
  – locks on the rope even if grabbed during the fall
- Simple to use, and effective:
  – moves up or down the rope, without any manual manipulation of the device
  – easy to install and remove at any point on the rope
  – it can be used with an energy absorber to work at a distance from the rope: the ASAP’SORBER European version or ASAP’SORBER AXESS allows uses of up to 250 kg in two-person rescue situations

Specifications

E & OE | Prices are subject to change without notice | Copyright - All Rights Reserved

Colorex Ltd
7 Fitzherbert St, Petone, Wellington 5012
PO Box 38 453, Wellington Mail Centre 5045
Phone: 04 587 0400, Email: sales@colorex.co.nz
www.colorex.co.nz

- Materials: aluminum & stainless steel
- Weight: 370g (295 g for ASAP and 75g for OK TRIACT-LOCK)
- Certifications: CE EN 12841 type A when used with an ASAP'SORBER and an EN 1891 type A 10 to 13mm rope
- Certifications: CE EN 353-2 when used with an ASAP'SORBER nergy absorber and an AXIS 11mm or PARALLEL 10.5mm rope with a sewn termination
- Certifications: EAC when used with an ASAP'SORBER and an EN 1891 type A 10 to 13mm rope

Petzl ASAP'Sorber

- Connects the ASAP or ASAP LOCK mobile fall arrester to the harness
- Allows the user to keep the rope at a distance in order to:
    - Declutter the work area
    - Protect the rope from sharp tools and molten metal splash
- Absorb the energy of a fall by the tearing of specific stitching
- Zippered fabric pouch protects the energy absorber from abrasion and other damage while allowing for regular inspection of the absorber
- Ends equipped with STRING to hold the connector in position and protect the webbing from abrasion
- Available in two lengths for a choice of the best balance between distance from the rope and reducing the fall length

Specifications

- Materials: nylon & polyester
- Certifications: CE EN 12841 type A and CE EN 353-2 when used with an ASAP or ASAP LOCK mobile fall arrester
- Certifications: CE EN 355, EAC

E & OE | Prices are subject to change without notice | Copyright - All Rights Reserved