



ZERO Kernmantle Static Rope 10.5mm ZT105

Brand: Zero
Code: C5702

\$6.50 + GST \$7.48 incl. GST

Description

ZERO Kernmantle Static Rope 10.5mm ZT105

For use in industrial abseiling, general industry and rescue lifeline use, work positioning and restraint. 10.5mm kernmantle is rated to 3,084kg. Static rope. For pre-cut lengths see below, any length up to 1000m available. Priced per metre, please specify the quantity of metres required.

Features

- Core / cover material: Polyamide
- Length per unit mass: 14.2 m/kg
- Breaking force: 3,084kg
- Knot breaking force: 1,510kg
- Impact strength index: min 3
- Elongation @ 80 kg / 375 kg: 2.5% / 9.4%
- Elongation @ break: >20%
- Knot-ability ratio: 1.0
- Sheath slippage: 1.0 mm
- Colourfast to water / rubbing / light: 4-5 / 4-5 / 6-7
- Additional information not covered by AS 4142:
- Static strength with figure of 8 knot (15kN / 3 mins): pass (broke at 18.8kN)
- Core / complete rope ratio: 52%

Product Specification

<https://colorex.co.nz/shop/products/height-safety/rope-ropelines/zero-kernmantle-static-rope-10-5mm-zt-10-5/>





YOUR NO 1 TRADE SHOP
COLOREX
TRADE & HIRE

Colorex Ltd

7 Fitzherbert St, Petone, Wellington 5012

PO Box 38 453, Wellington Mail Centre 5045

Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz

- Cover / complete rope ratio: 48%
- Static strength with sewn eyes: 22.7kN

Product Specification

<https://colorex.co.nz/shop/products/height-safety/rope-ropelines/zero-kernmantle-static-rope-10-5mm-zt-10-5/>

Page 2

E & OE | Prices are subject to change without notice | Copyright - All Rights Reserved



YOUR NO 1 TRADE SHOP
COLOREX
TRADE & HIRE

1713526169