Colorex Ltd



7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz



Festool Edge Bander Conturo KA 65 Plus Edge Bander Set with Systainer

Brand:Festool **Code:** C2114-1

\$5,315.35 +GST \$6,112.65 incl. GST

Description

Festool Edge Bander Conturo KA65 Plus Edge Bander Set with Systainer

With an integral system that accompanies the new CONTURO KA 65 from the workpiece being prepared right through to the perfect edge finish. For classic furniture edging or manufacturing shaped parts with convex or concave curves. For finishing work in wood, melamine or plastic. For variable edge heights and material thicknesses up to 3mm

Features:

- For attaching edging to rectangular components, inner corners, curves, radii, convex and concave shapes. Internal radius up to 50mm, minimum external radius of 25mm 30mm. Gluing inclined edges at an angle of 0 47º
- Suitable for all standard edge materials, from wood and plastic to melatine, for edge heights of 18mm 65mm and edge thicknesses of 0.5mm – 3mm
- Four different adhesive colours guarantee the perfect join quality and with the new polyurethane adhesive, waterproof and heat resistant gluing is now easy
- Easy, clean and efficient work as well as quick colour changes thanks to the unique cartridge gluing system
- Precision glue application for a perfect join quality and maximum adhesion
- The display conveniently guides you through all working steps and also provides important information
- Nozzle system that is easy to clean
- Self contained system that prevents the unwanted escape of glue
- The horizontally mounted application system guarantees perfect weight distribution, while the pressure on the handles is transferred to the contact roller automatically for effortless work

Product Specification



Colorex Ltd



7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz

- Device housing does not heap up, ensuring safety while working
- For narrow radii and awkward spots the additional roller increases the bedning radius of the edge and provides an additional pressure point during positioning for better adhesion
- Trimming plastic edging, even up to abutting surfaces

Suitable For:

- Affixing wooden, plastic or laminated plastic edging to panel materials
- Possible to attach edging to simple rectangular components or more complex free forms
- Suitable for mobile use, for rapidly reworking edges in situ
- Suitable for stationary use and small batches, straight edges, free form elements and gluing inclined edges, angle from 0-47°

Specifications

Heating Time	8 minutes
Power Lead Type	Fixed Lead
Power Source	Corded
Power Consumption	1200W
Motor Type	Brushes
Melting Temperature	100º - 210º
Feed Rate	3m every 4 minutes
Edge Height	18mm - 65mm
Edge Thickness	0.5mm - 3mm
Inner Radius	>50mm
Tool Weight	7.9kg



