Colorex Ltd



7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz



Festool Edge Bander Conturo KA 65 Set with **KB-KA65** in Systainer

Brand:Festool Code: C2114-2

\$5,865.85 +GST \$6,745.73 incl. GST

Description

Festool Edge Bander Conturo KA65 Set with KB-KA65 in Systainer

Edging straight surfaces, curves, radii, convex and concave shapes as well as internal corners is easy with the CONTURO. Edging can even be attached to mitred edges to an outstanding quality with the stationary unit. Quick, easy and clean ideal for shaped parts and small batches. Suitable for machining all types of wood, plastic or melamine edging with a height of 18 - 65 mm and edge thickness of 0.5 - 3.0 mm (depending on material). The CONTURO is packed away safely in a SYSTAINER, extremely mobile and delivers a perfect edge quality, even in combination with system accessories.

Main Applications

- Affixing wooden, plastic or laminated plastic edging to panel materials
- Attach edging to simple rectangular components or more complex free forms
- Suitable for mobile use, for rapidly reworking edges on site
- Suitable for stationary use and small batches, straight edges, free form elements and gluing inclined edges, angle from 0-47°

Strengths And Benefits

- Clean and efficient cartridge gluing system
- Adhesive melts according to requirements and does not boil, discolour or deteriorate
- Stationary application for greater versatility
- Easy to handle, perfect ergonomics, clear view of the workpiece

Product Specification

-set-with-kb-ka65-in-systainer/







7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz

• Nozzle system that is easy to clean, machine housing does not heat up, allowing safe working progress

Specifications

Power	1,200W
Mains frequency	50/60Hz
Edging height	18 - 65mm
Edging thickness	0.5 - 3.0mm
Inner radius	> 50mm
Heating time	approx. 8 min
Melting temperature setting range	100 - 210°C
Feed speed 1st gear	2m/min
Feed speed 2nd gear	4m/min
Weight	7.9kg

What's Included

Qty	Description
1	Edge banding machine
1	Support base with handle
4	Natural EVA adhesive
1	SYS 4 T-LOC Systainer
1	Edging holder
1	Additional roller
1	Trimming machine
1	Scraper
1	Base runner scratch protector
3	Felt pads
5	Polishing felt
20	Abrasive sheets P320

Product Specification





Colorex Ltd



7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz

Qty	Description
1	Hand sanding block
5	StickFix sanding cloth S 800
1	Polish MPA 6000