

7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz



John Bull Himalaya 2.0 Safety Boot

Brand: John Bull \$224.00+GST

Options

Description	Price
Size 5	\$224.00
Size 13	\$224.00
Size 14	\$224.00
Size 7	\$224.00
Size 12	\$224.00
Size 10	\$224.00
Size 11	\$224.00
Size 8	\$224.00
Size 9	\$224.00
Size 6	\$224.00
	Size 5 Size 13 Size 14 Size 7 Size 12 Size 10 Size 11 Size 8 Size 9

Description

John Bull Himalaya 2.0 Safety Boot - 4545

Claret Bullhide leather lace up safety boot

The most popular boot in the John Bull range – these are your general workhorse boot. The Himalaya can go anywhere and do anything.

With a bull bar too these are sure to quickly become your favourite boots – especially now they're adorned with the latest soling technology – CushionCore

Loved by construction workers, general tradies, electricians, landscapers, farmers, and workers in manufacturing, transport, heavy industry and mining.

Product Specification





Colorex Ltd



7 Fitzherbert St, Petone, Wellington 5012 PO Box 38 453, Wellington Mail Centre 5045 Phone: 04 587 0400, Email: sales@colorex.co.nz

www.colorex.co.nz

Features:

- New CushionCore comfort technology absorbs and disperses energy as your heel strikes down while generating rebound at the front of your foot
- Dual-density midsole World first technology of two compounds skilfully injected into the midsole providing superior shock absorption at the heel and providing rebound at the forefront as you step
- TPU outsole with aggressive self-cleaning tread pattern providing superior grip, stability and abrasion resistance
- Super cushioning Comf2Bull airflow footbed of soft PU that's also antibacterial and washable
- Moulded PU Bull Bar scuff cap
- Extra heavy duty TPU toe guard for extra scuff protection
- Fully lined with padded collar and tongue
- Broad fitting 200 joule impact resistant type 1 steel toe cap
- Certified to Standard AS/NZS 2210.3.2009-Classification 1-ID 2815
- Certified to: Standard ASTM F2413-11 including electrical shock resistance (Clause 5.5)